

Unpacking and Placement

Uncrating

1. Unscrew and remove top panel.
2. Unscrew and remove "outer panels"
 - a. These are opposing panels that are screwed into the other 2 "inner" panels.
3. Remove packages of media, soaps, etc.
4. Remove 2x4 blocks securing the machine to the pallet.
5. Lift machine off of pallet from the front for easy placement.

Machine Placement

1. 3 feet of clearance are recommended on each side of the machine for easy maintenance.
2. Ground must be level for machine placement.
3. Place included foot pads in the chosen area.
4. Using a forklift, place the machine on the footpads.
 - a. For easy placement, lower the machine slowly and adjust foot pads to be centered with the machine's feet.
5. **DO NOT BOLT OR SECURE MACHINE TO THE FLOOR OR WALL.**
 - a. The foot pads provide vibration absorption vital to the operation of the machine.

Electrical

Electrical Hookup

- The facility should contact a qualified electrician to determine what type of plug or connection should be used to match the facility's existing electrical infrastructure.
- The voltage required for the DCPC250 & DCPC500 is 208VAC – 240VAC, 50Hz/60Hz, single-phase.
- Power to the unit should be provided by a minimum of 12/3 SJOOW power cord.
 - Connected to a circuit protected by either circuit breaker or fuse rated at
 - DCPC250: 16 Amps
 - DCPC500: 20 Amps
- The electrical panel can be accessed through the front control panel by removing the screws on the face. It should only be accessed by a qualified electrical.

Specifications

DCPC250 Specifications

Max Capacity	0.25 Cubic Feet (7.07 Liters)
Barrel Capacity	0.0625 Cubic Feet (1.77 Liters)
Barrel Dimensions	W 4.5" (11.4cm) x H 6" (15.2cm)
Machine Dimensions	D: 30.1" x W: 28.5" x H: 51.5"
Machine Weight	~480lbs
Power Requirements	208/240 (± 10%) VAC, 50/60Hz, 1Ø, 16A
Main Drive/Motor	1HP, Inverter-Controlled, Single-Phase
Operating Volume	Under 70 Decibels
Compressed Air	Not Required

DCPC500 Specifications

Max Capacity	0.50 Cubic Feet (14.16 Liters)
Barrel Capacity	0.125 Cubic Feet (3.54 Liters)
Barrel Dimensions	W 6" (15.25cm) x H 6.75" (17.15cm)
Machine Dimensions	D: 32" x W: 32" x H: 55"
Machine Weight	~600lbs
Power Requirements	208/240 (± 10%) VAC, 50/60Hz, 1Ø, 20A
Main Drive/Motor	2HP, Inverter-Controlled, Single-Phase
Operating Volume	Under 70 Decibels
Compressed Air	Not Required